

DS-PDEB1-EG2-WE(B) Wireless Emergency Button

The panic button is an updated version of current wireless emergency button with water-proof feature. It is flexible to be fixed in any places even in strong humid environment.



- Effective emergency button
- Fully remote configurable through APP
- Multiple enrollment methods and easy installation design
- Frequency hopping against jamming for reliable transmission
- IP66 water proof

▪ Specification

Feature	
Button	1
Tamper Protection	Front,Rear
Environment Temperature Indicator	Support
Signal Strength Indicator	Support
Interface	
LED Indicator	Blue (alarm)
Transmission	
Transmission Technology	Tri-X Wireless
Transmission Method	Two-Way RF Wireless
Transmission Frequency	868MHz
Transmission Security	AES-128 Encryption
Transmission Range(Free Space)	1.2Km
Frequency Hopping	Support
Enrolling Method	Power up,Remote ID,QR Code
Electrical Characteristics	
Standard Battery Life	Up to 3 years (standby time)
Power Supply	Battery powered
Battery Type	CR2450 x 1
Typical Voltage	3V
General	
Operation Temperature	-10°C to 55°C (14°F to 131°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Operation Humidity	10% to 90%
IP Rate	IP66
Dimension(WxHxD)	63.8 mm × 63.8 mm × 18.4 mm
Weight	57.5 g
Mounting Method	Wall
Application Scenario	Indoor, Humid environment especially

▪ Available Model

DS-PDEB1-EG2-WE(B)

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

