Consumer Enterprise

Language

GIGABYTE

PRODUTOS ▼

SUPORTE

INSIGHT

NEWS

ONDE COMPRAR









Home > Placas-mãe > H410M K

H410M K (rev. 1.0)

rev. 1.1

Características Especificação Suporte Compre Intel® H470 Chipset ☐ Lista de Comparativos 1. LGA1200 package: Support 10th Generation Intel[®] Core™ i9 processors/Intel[®] Core[™] i7 processors/Intel[®] Core[™] i5 processors/Intel[®] Core™ i3 processors/Intel[®] Pentium[®] **CPU** processors/Intel® Celeron® processors 2. L3 cache varies with CPU (Please refer "CPU Support List" for more information.) 1. Intel[®] H470 Express Chipset Chipset Memória 1. 10th Generation Intel[®] Core[™] i9/i7 processors:



Compare Compare up to 4 models in this product category Compare Clear All 5. Support for ECC Un-buttered DIIVIN 1KX8/2KX8 memory modules (operate in non-ECC mode) 6. Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memory modules 7. Support for Extreme Memory Profile (XMP) memory modules (Please refer "Memory Support List" for more information.) Integrated Graphics Processor-Intel[®] HD Graphics support: 1. 1 x HDMI port, supporting a maximum resolution of **Gráficos** 4096x2160@30 Hz **Onboard** * Support for HDMI 1.4 version and HDCP 2.3. (Graphics specifications may vary depending on CPU support.) Áudio 1. Realtek® Audio CODEC 2. High Definition Audio 3. 2/4/5.1/7.1-channel * You can change the functionality of an audio jack using the



Compare	0 Compare up	to 4 models in this product category
		Clear A
		CPU:
	Slots de Expansão	1. 1 x PCI Express x16 slot, supporting PCIe 3.0 and running at x16
		Chipset:
		1. 1 x PCl Express x1 slot, supporting PCle 3.0 and running at x1
		Chipset:
	Interface de Armazenamento	1. 1 x M.2 connector (Socket 3, M key, type 2280 SATA and PCle 3.0 x4/x2 SSD support)2. 2 x SATA 6Gb/s connectors
		Support for RAID 0, RAID 1, and RAID 5 Intel [®] Optane™ Memory Ready
	USB	Chipset:
		1. 4 x USB 3.2 Gen 1 ports (2 ports on the back panel, 2 ports



Compare	Compare up to 4 models in this product category				
	Conectores Internos I/O	3. 1 x CPU ran neader 4. 1 x system fan header 5. 1 x RGB LED strip header 6. 1 x M.2 Socket 3 connector 7. 2 x SATA 6Gb/s connectors 8. 1 x front panel header 9. 1 x front panel audio header 10. 1 x USB 3.2 Gen 1 header 11. 1 x USB 2.0/1.1 header 12. 1 x serial port header 13. 1 x Clear CMOS jumper	Clear All		
	Conectores Painel Traseiro	1. 1 x HDMI port 2. 2 x USB 3.2 Gen 1 ports 3. 4 x USB 2.0/1.1 ports 4. 1 x RJ-45 port 5. 3 x audio jacks			



Compare up to 4 models in this product category Compare Clear All 2. Temperature detection 3. Fan speed detection Monitoramento 4. Fan fail warning H/W 5. Fan speed control * Whether the fan speed control function is supported will depend on the cooler you install. 1. 1 x 128 Mbit flash BIOS 2. Use of licensed AMI UEFI BIOS 3. PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0 Características 1. Support for APP Center **Exclusivas** * Available applications in APP Center may vary by motherboard model. Supported functions of each application may also vary depending on motherboard specifications. @BIOS Ambient LED

This website uses cookies to provide you a more personalized and responsive service. By using this website you agree to our use of cookies. If you require more information or prefer not to accept cookies please visit our Privacy Policy.

FacyTuna



Compare	Compare up to 4 models in this product category		
	Pacote de Software	 Norton[™] Internet Security (UEIVI version) LAN bandwidth management software 	Clear All
	Sistema Operacional	 Support for Windows 11 64-bit Support for Windows 10 64-bit 	
	Form Factor	1. Micro ATX Form Factor; 22.6cm x 18.5cm	
	Observação	 Due to different Linux support condition provided by chipset vendors, please download Linux driver from chipset vendors' website or 3rd party website. Most hardware/software vendors may no longer offer drivers to support Win9X/ME/2000/XP. If drivers are available from the vendors, we will update them on the GIGABYTE website. 	

