



Home > Placas-mãe > [B760M H DDR4](#)

B760M H DDR4 (rev. 1.0)

[Características](#) [Especificação](#) [Suporte](#) [Compre](#)

Intel® B760 Chipset

[Lista de Comparativos](#)

CPU

LGA1700 socket: Support for the 14th, 13th, and 12th Generation Intel® Core™, Pentium® Gold and Celeron® Processors
L3 cache varies with CPU
(Please refer to "CPU Support List" for more information.)

Chipset

Intel® B760 Express Chipset

Memória

Support for DDR4 3200/3000/2933/2666/2400/2133 MT/s memory modules
2 x DDR4 DIMM sockets supporting up to 64GB (32 GB single DIMM capacity) of system memory
Dual channel memory architecture
Support for ECC Un-buffered DIMM 1Rx8/2Rx8 memory modules (operate in non-ECC mode)
Support for non-ECC Un-buffered DIMM 1Rx8/2Rx8/1Rx16 memorv

This website uses cookies to provide you a more personalized and responsive service. By using this website you agree to our use of cookies. If you require more information or prefer not to accept cookies please visit our [Privacy Policy](#).



Compare

0

Compare up to 4 models in this product category

Compare

Clear All

Gráficos Onboard

- 1 x HDMI port, supporting a maximum resolution of 4096x2160@60 Hz

* Support for HDMI 2.0 version and HDCP 2.3.

(Graphics specifications may vary depending on CPU support.)

Áudio

Realtek[®] Audio CODEC
High Definition Audio
2/4/5.1/7.1-channel

* You can change the functionality of an audio jack using the audio software. To configure 7.1-channel audio, access the audio software for audio settings.

Support for S/PDIF Out

LAN

Realtek[®] GbE LAN chip (1 Gbps/100 Mbps)

Slots de Expansão

CPU:

- 1 x PCI Express x16 slot, supporting PCIe 4.0 and running at x16

Chipset:

- 1 x PCI Express x1 slot, supporting PCIe 3.0 and running at x1

Interface de

CPU:

This website uses cookies to provide you a more personalized and responsive service. By using this website you agree to our use of cookies. If you require more information or prefer not to accept cookies please visit our Privacy Policy.



Compare **0**

Compare up to 4 models in this product category

Clear All

USB

Chipset:

- 6 x USB 3.2 Gen 1 ports (4 ports on the back panel, 2 ports available through the internal USB header)
- 6 x USB 2.0/1.1 ports (2 ports on the back panel, 4 ports available through the internal USB headers)

Conectores Internos I/O

- 1 x 24-pin ATX main power connector
- 1 x 8-pin ATX 12V power connector
- 1 x CPU fan header
- 2 x system fan headers
- 1 x RGB LED strip header
- 2 x M.2 Socket 3 connectors
- 4 x SATA 6Gb/s connectors
- 1 x front panel header
- 1 x front panel audio header
- 1 x S/PDIF Out header
- 1 x USB 3.2 Gen 1 header
- 2 x USB 2.0/1.1 headers
- 1 x Trusted Platform Module header (For the GC-TPM2.0 SPI/GC-TPM2.0 SPI 2.0 module only)

This website uses cookies to provide you a more personalized and responsive service. By using this website you agree to our use of cookies. If you require more information or prefer not to accept cookies please visit our Privacy Policy.



Compare **0**

Compare up to 4 models in this product category

Clear All

Controlador I/O iTE[®] I/O Controller Chip**Monitoramento H/W**

Voltage detection
 Temperature detection
 Fan speed detection
 Water cooling flow rate detection
 Fan fail warning
 Fan speed control

* Whether the fan speed control function is supported will depend on the cooler you install.

BIOS

1 x 128 Mbit flash
 Use of licensed AMI UEFI BIOS
 PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Características Exclusivas

Support for GIGABYTE Control Center (GCC)

* Available applications in GCC may vary by motherboard model. Supported functions of each application may also vary depending on motherboard specifications.

Support for Q-Flash

This website uses cookies to provide you a more personalized and responsive service. By using this website you agree to our use of cookies. If you require more information or prefer not to accept cookies please visit our Privacy Policy.

